i-SENSYS LBP3310 Specifications

Engine Specs:	
Printing speed	Mono 26 pages (A4)
Printing method	Mono LASER BEAM PRINTING
Duty Cycle	10,000 pages
Fixing method	On-Demand fixing
Resolution	600 x 600 dpi (2400 x600 dpi with Automatic Image Refinement)
Warm-up time	0 seconds from Standby, Approx. 8 seconds from POWER ON
First print	Approx. 6.5 seconds or less
Toner cartridge	Standard: Cartridge 715: 3000 page yield at @ ISO 19752 High yield: Cartridge 715H: 7000 page yield at @ ISO 19752
Toner Save	Yes
Paper Input(standard)	250-sheet cassette/50-sheet multi-purpose tray (64 g/㎡)
Paper input (Option)	250-sheets x 1(PF-35P) (64 g/㎡)
Paper output	125sheets Face-down /1sheet Face-up
Paper size (Standard cassette & optional cassette)	A4, B5, A5, Legal, Letter, Executive, 16k Custom Paper Size (width 148.0 to 215.9 mm, length 210.0 to 355.6 mm)
Paper size (Multi-purpose tray)	A4, B5, A5, Legal, Letter, Executive, Envelope DL, Envelope COM10, Envelope C5, Envelope Monarch, Index Card, Custom Paper Size (width 76.2 to 215.9 mm, length 127.0 to 355.6 mm)
Duplex printing	Yes (built-in as standard:A4,Legal, Letter) 13.3ipm
Power requirements	220-240V(±10%) 50/60Hz (±2Hz)
Power consumption	Approx. 392W (Average during operation), Approx. 4W (Average during sleep)
Noise level	Max. 55 dB [A] or less (during operation) Background noise only (during standby)
Dimensions (W x D x H)	399.7 x 378.6 x 258mm
Weight	Approx. 11.2kg (without cartridge) Approx. 12kg (with cartridge)
Cartridge weight	Cartridge 715: approx. 0.8 kg, Cartridge 715H: approx 1.0kg
Operating environment	Temperature: 10 to 32ºC (50 to 86ºF) Humidity 20 to 80%RH (no condensation)
Storage environment	Temperature: 0 to 35ºC (50 to 86ºF) Humidity 10 to 85%RH (no condensation)
Energy Star Compliant	Yes
Controller hardware spec	
Smoothing technology	AIR (Automatic Image Refinement) 2400 x 600 dpi equivalent
CPU	TBC
RAM (Standard)	8MB with CAPT and Hi-SCoA
Interface (Standard)	USB 2.0 High Speed

Interface (Optional)	10Base-T/100Base-TX (NB-C2)
Controller software spec	
PDL (Standard)	CAPT (Canon Advanced Printing Technology) with Hi-SCoA
Supported PC OS	Windows 2000/XP/Server 2003/Vista(32bit, 64bit) Linux (Online distribution only)
Mac Compatible	Mac OS X Version 10.2.x, 10.3.x, 10.4.x, 10.5.x (Online distribution only)

Please note that these specifications are subject to change